

HATTAT C 3055 / C 3065 / C 3080
TECHNICAL SPECIFICATIONS

Model	C 3055 4WD	C 3065 4WD	C 3080 4WD
Engine	Perkins	Perkins	Perkins
Emission level	Stage 3A	Stage 3A	Stage 3A
Engine serial code	1103D-33TA	1103D-33TA	1103D-33TA
Rated engine power [kW/hp/rpm] [ISO14396]	44 / 60 / 2200	50 / 68 / 2200	55,9 / 76 / 2200
Max. torque [Nm/rpm]	251 / 1400	280 / 1400	310 / 1400
Capacity [cm³] / no of cylinders	3 / 3300	3 / 3300	3 / 3300
Cylinder diameter x stroke [mm]	105 / 127	105 / 127	105 / 127
Type of air filter	Dry type, with warning indicator	Dry type, with warning indicator	Dry type, with warning indicator
Aspiration	Turbocharger&Intercooler	Turbocharger&Intercooler	Turbocharger&Intercooler
Fuel tank [lt]	70	70	70
Transmission			
Type of gearbox	12F+12R Synchro Shuttle	12F+12R Synchro Shuttle	12F+12R Synchro Shuttle
Gearbox clutch	Dry type double disc clutch	Dry type double disc clutch	Dry type double disc clutch
Speeds [km/h-rpm]	34-2200	34-2200	34-2200
Differential Lock & Powered Front Axle			
Differential lock engagement	Mechanical	Electro-Hydraulic	Electro-Hydraulic
4WD engagement	Mechanical	Electro-Hydraulic	Electro-Hydraulic
PTO			
PTO Type	Independent	Independent	Independent
PTO rpm - engine rpm	540-1890 / 540E-1594	540-1890 / 540E-1594	540-1890 / 540E-1594
Brake			
Brake	Hydraulically operated multi disc brakes	Hydraulically operated multi disc brakes	Hydraulically operated multi disc brakes
Parking brake	Mechanical with hand lever operated	Mechanical with hand lever operated	Mechanical with hand lever operated
Activate of 4WD by brake	-	Standard	Standard
Pneumatic trailer brake	Optional [available in cabin models only]	Optional [available in cabin models only]	Optional [available in cabin models only]
Auxiliary Hydraulics & Rear Hydraulic Lift			
Max. pump capacity, pump pressure [(lt/min)/bar]	45/195	45/195	45/195
Functions	Position, draft control, Auto-Lift	Position, draft control, Auto-Lift	Position, draft control, Auto-Lift
Auxiliary hydraulic [output/valves]	4/2	4/2	4/2
Max. lifting force [kg]	2200	3000	3000
Dimensions and Weights			
Weight [without ballast weights] [kg] [rops/cabin]	2900/3140	2900/3140	2900/3140
Front ballast weight [kg]	6x22	8x22	8x22
Rear ballast weight [kg]	2x45	2x45-2x70	2x45-2x70
Total length, with front weights [mm]	4050	4050	4050
Wheelbase [mm]	2030	2030	2030
Front wheel track settings [mm]	1340-1488	1340-1488	1340-1488
Rear wheel track settings [mm]	1306-1706	1306-1706	1306-1706
Overall width [mm]	1621-2169	1621-2169	1621-2169
Overall height [mm] [rops/cabin]	2440/2565	2440/2565	2440/2565
Ground clearance [mm]	365	468	468
Tires			
Option 1 [front]	280/70R20	300/70R20	300/70R20
Option 1 [rear]	14,9/13-28	380/85R30	380/85R30
Option 2 [front]	280/70R18	280/85 R20	280/85 R20
Option 2 [rear]	340/85R28	12,4/11-36	12,4/11-36
Option 3 [front]	300/70R20	300/70R20	300/70R20
Option 3 [rear]	14,9/13-30	14,9/13-30	14,9/13-30
Option 4 [front]	300/70R20	-	-
Option 4 [rear]	380/85R30	-	-

Hattat Traktör Sanayi ve Ticaret A.Ş. has the right to change the designs and technical information specified in this brochure.